





ZT4-LV

Flatbed for different types of transport

ZT4-LV for hooklifts is durable and developed for safe transport with an easy-to-work gate system and easy spreading of loads. It is equally suitable for loading and unloading piece goods and transporting pallets.

The ZT4 has a built-in locking system for the sides, which is guaranteed to save your back as well as time and money.

PRODUCT BENEFITS

- Swedish-made flatbed.
- High load capacity.
- Light, strong and durable.
- The base in high-strength steel.
- Lightly worked construction with locking function on side gates.
- Good protection against corrosion.
- Adapted to standard SS 3021.







Specification example

Internal length from 4500 to 7300 mm with 100 mm intervals.

External width 2550 alt. 2600 mm.

Internal width 2490/2458 alt. 2440/2408 mm.

Subframe built according to standard SS 3021.

Bar height 1450 mm.

Bottom 5 mm thick high-strength steel reinforced with transverse bottom profiles.

Front wall 3 mm of high-strength steel. Joint front wall of pipe with expanded metal.

Side gates in 25 alt. 40 mm anodized aluminum plank. Height from 600 to 1200 mm with 100 mm intervals.

Spreader gate 40 mm anodised aluminum plank, front hung. 100 mm higher than the sides.

Automatic tailgate pneumatic actuation. Height 250 alt. 400 mm, of high-strength steel.

Characteristics

The flatbed is light and rigid in high-strength steel with longitudinal beams and bottom profiles.

Locking construction on the side gates for easy handling.

Low weight for maximum load capacity.

Other options

Spreader release instead of automatic tailgate.

Asphalt plates for the automatic tailgate for extra overhang when feeding the asphalt paver.

Extension gates of 25 mm anodized aluminum plank, type on stick.

Bottom in 6 mm thickness.

Automatic tailgate with hydraulic operation.

Tie hooks inside and outside.

Spreader gate can be opened as a door.

Hooks for lifting straps, inside front wall.

Short parcel gate that can be opened as a door.

Kinnegrip's posts with associated sides with K20 locking.

